

REAR VIEW MIRROR W/ STANDARD CAMERA SPECIFICATIONS



REAR VIEW MIRROR MONITOR SPECS

TYPE	TFT LCD
SCREEN SIZE	7"
DOT RESOLUTION	800 X 3 (RGB) X 480
DISPLAY FORMAT / CONTRAST	16:9 / 500:1
DISPLAY BRIGHTNESS	400cd/m ²
VIEWING ANGLE	90°
VIDEO INPUT	Video Input
VIDEO SOURCE	1Vp - p, 75Ω
POWER SUPPLY	DC 9/32V
POWER CONSUMPTION	5W
OPERATING TEMPERATURE	-30°C ~ +80° C
VIDEO SYSTEM	Auto NTSC/PAL
OVERALL DIMENSIONS	9" (L) x 4.5" (H) x 1" (D)
WEIGHT	400G
IMPACT RATING	5G
DOT PITCH	0.192 (H) X 0.1805 (V)
SYNC SYSTEM	Internal

BACKUP CAMERA SPECS

CAMERA	1/3" Sharp® Color CCD
PICTURE ELEMENTS	410,000 pixels
GAMMA CORRECTION	R=0.45 to 1.0
IMAGE SENSOR	620 TV lines
	PAL: 752 (H) x 582(V) NTSC: 811 (H) x 507(V)
LENS	2.5mm
VIEW ANGLE	130°
WATERPROOF RATING	IP69K
SYNC SYSTEM	Internal Synchronization
INFRA-RED DISTANCE	50 Feet (18 Infrared)
USABLE ILLUMINATION	0 Lux (IR ON)
POWER SOURCE	DC 9V-32V
S/N RATIO	More than 48dB
ELECTRONIC IRIS	1/50, 160-1/100,000sec
VIDEO OUTPUT	1Vp.p 75ohm
IR SWITCH CONTROL	ACDS Automatic Control
VIBRATION & SHOCK RATING	20G / 100G
OPERATING TEMPERATURE	-30°C ~ +70°C / RH 95% Max
STORAGE TEMPERATURE	-30°C ~ +85°C / RH 95% Max
NET WEIGHT	22 oz