

RVS-659 CAMERA COMPLIANCE STATEMENT

Rear View Safety, Inc. hereby certifies that our RVS-659 camera is FMVSS 111 compliant when installed on vehicles between 5"-96" inches off the ground.

While we recommend the camera to be installed at the center point of the vehicle, it can be mounted off-center according to the following specs and still maintain compliance:

Min Height (5 inches) – 3 inches off center

Mid Height (50 inches) – 12 inches off center

Max Height (96 inches) – 1 inch off center

Camera Requirements:

The camera will both activate and deactivate automatically when vehicle is put and taken out of reverse, respectively (with correct monitor settings).

The camera will only deactivate when the vehicle is put out of reverse, or the driver changes the screen channel (with correct monitor settings).

The camera is rated IP68 and was put through a corrosion, humidity and temperature test.

The camera has a 170° viewing angle, which, when positioned correctly will be able to capture all seven pylons required in order to be compliant, as shown on diagram:

Please note that this statement **does not** certify your vehicle's compliance to the FMVSS 111 regulation, but rather, validates that our camera has the above requirements to consent to the law. It is the sole responsibility of the installer/manufacture/up-fitter to ensure vehicle meets requirements with camera installed.

For further information, please contact:

Dylan Lew
FMVSS 111 Specialist
dlew@rearviewsafety.com
Rear View Safety – A Safe Fleet Company

