

Split Platform



High Capacity Floor Deployed Platform



Highly engineered, in the floor platform,
with a 1,000 lb. weight capacity

- 1,000 lb. weight capacity can accommodate a ramp or ladder in parallel or perpendicular positions
- Serrated, open grating work surface offers slip-resistant access in any work environment or weather conditions
- 1-1/2" space between panel segments allows the platform to straddle floor-support beams within the tunnel

Installs at the OEM

| Split Platform | | | | | | |
|----------------|----------|---------|-------|-------------|---------|-----------------|
| MODEL | MATERIAL | WIDTH | DEPTH | # OF PANELS | WEIGHT | WEIGHT CAPACITY |
| 124-APD-022 | Aluminum | 33-5/8" | 33" | 3 | 74 lbs. | 1,000 lbs. |
| 349-APD-027 | Aluminum | 34-1/2" | 33" | 3 | 66 lbs. | 1,000 lbs. |
| 349-APD-026 | Aluminum | 43" | 33" | 4 | 90 lbs. | 1,000 lbs. |

FM-8.2-2065 / Rev C / 10-20-21

Copyright ©2021 Safe Fleet and its subsidiaries. All rights reserved. No part of this publication may be reproduced by any means without written permission from Safe Fleet. The information in this publication is believed to be accurate. However, Safe Fleet does not make any representation or warranty to that effect and does not assume responsibility for any consequences resulting from use of such information. Revisions or new editions of the publication may be issued (or not issued) in our discretion to incorporate such changes.

1.800.827.3692
safefleet.net

