

Randall Straight Walkramp

Highly-Engineered, Ultra-Durable, Safety Walkramp



Safety walkramp providing drivers an all-weather, aggressive walk surface.



Easy to Repair

Walk surface panels are constructed from aluminum alloys and are easily repairable and replaceable.



Superior Traction

Aggressive, all-weather surface is extruded to prevent cracking and provide a safe walking ramp for drivers.



Ergonomic

Panel contains an all steel toe plate with ergonomic hand grips for safe operation.

Randall Straight Walkramp

Optional Lift Assist



Two styles of lift assists are available – long and short, depending on the dimension from the enclosure to the trailer floor.

Side Bracket



Stress points are taken care of with a longer arm and multiple fasteners.

Optional Enclosure



Two enclosure types are available – open and closed.

Optional Safety Chain



Optional enclosure safety chain is available.

Specifications

RAMP LENGTH	RAMP WIDTH*	USABLE WIDTH	RAMP HEIGHT	RECOMMENDED DECK HEIGHT	APPROXIMATE WEIGHT	LOAD CAPACITY**
16'	26.25"	24.375"	4.625"	56" - 66"	127 lbs.	1000 lbs.
16'	31.0"	29.625"	4.625"	56" - 66"	145 lbs.	1000 lbs.
14'	26.25"	24.375"	4.625"	46" - 55"	115 lbs.	1000 lbs.

* Widest outer dimension

**Testing of ramps was conducted between 15 and 20 degrees. Load tests were conducted with a 500 lbs. load and 225 lbs. driver.

FM-8.2-3003 / Rev B / 06/20/2022

Copyright ©2022 Safe Fleet and its subsidiaries. All rights reserved. No part of this publication may be reproduced by any means without written permission from Safe Fleet. The information in this publication is believed to be accurate. However, Safe Fleet does not make any representation or warranty to that effect and does not assume responsibility for any consequences resulting from use of such information. Revisions or new editions of the publication may be issued (or not issued) in our discretion to incorporate such changes.

R RANDALL
A Safe Fleet Brand

1.877.630.7366
safefleet.net

SAFE FLEET
Driving Safety Forward™